

Radio Accessories



H-250/U/MLT Handset
H-182SS/MLT Single-Sided Headset
H-161F/MLT Double-Sided Headset

Manufactured in Greece by


MILTECH
HELLAS S.A.

Radio Accessories

H-182SS/MLT Single-Sided Headset

Characteristics:



- Lightweight, durable and comfortable single-sided headset for tactical applications.
- Intended for use with all radios and telephone sets that comprise the U-183/U connector.
- Modified version of the H-182SS Headset, terminated with a single connector in accordance to the requirements of the Hellenic Army.
- PTT switch U94A/U
- Single U-229/U connector
- Spiral Cord, 1.80m from switch
- Color: Black
- Temperature Range: -5 / +65°C
- Meets SPECs per MIL-H-83511 for: Temperature, Humidity, Immersion, Vibration, Blast, Shock, Salt fog, Sand & Dust, Fungus
- Microphone M138/G: Dynamic, 300-3500 Hz
- Sensitivity: -56dB @ 1kHz re 103dB SPL
- Impedance: 150Ω, ±15Ω @ 1kHz
- Distortion: <6% @ 114dB SPL
- Single earphone: Dynamic, 100-3500 Hz
- Sensitivity: ≥105dB @ 1kHz re 1MW RMS
- Impedance: 1000Ω, ±10Ω @ 1kHz
- Distortion: <5% @ 100-3500 Hz

H-161F/MLT Double-Sided Headset

Characteristics:



- Lightweight, durable and comfortable double-sided headset for tactical applications.
- Intended for use with all radios and telephone sets that comprise the U-183/U connector.
- Modified version of the H-161F Headset, terminated with a single connector in accordance to the requirements of the Hellenic Army.
- PTT switch U94A/U
- Single U-229/U connector
- Spiral cord, 1.80m from switch
- Color: Black and Green
- Temperature Range: -5 / +65°C
- Meets SPECs per MIL-H-83511 for: Temperature, Humidity, Immersion, Vibration, Blast, Shock, Salt fog, Sand & Dust, Fungus
- Microphone M138/G: Dynamic, 300-3500 Hz
- Sensitivity: -56dB @ 1kHz re 103dB SPL
- Impedance: 150Ω, ±15Ω @ 1kHz
- Distortion: <6% @ 114dB SPL
- Double earphones: Dynamic, 100-3500 Hz
- Sensitivity: ≥105dB @ 1kHz re 1MW RMS
- Impedance: 1000Ω, ±10Ω @ 1kHz
- Distortion: <5% @ 100-3500 Hz

H-250/U/MLT Handset

Characteristics:



- Lightweight, durable and comfortable handset for tactical applications.
- Intended for use with all radios and telephone units that comprise the U-183/U connector.
- PTT switch with make/brake sequence
- U-229/U connector
- Spiral Cord, 2m.
- Color: Black
- Temperature Range: -20 / +65°C
- Meets SPECs per MIL-PRF-49078 for: Temperature, Humidity, Altitude, Immersion, Blast, Vibration, Shock, Bounce, Salt fog, Dust, Fungus
- Microphone: Dynamic, 300-3500 Hz
- Sensitivity: -56dB @ 1kHz re 103dB SPL
- Impedance: 150Ω, ±15Ω @ 1kHz
- Distortion: <6% @ 114dB SPL
- Earphone: Dynamic, 100-3500 Hz
- Sensitivity: ≥105dB @ 1kHz re 1MW RMS
- Impedance: 1000Ω, ±10Ω @ 1kHz
- Distortion: <5% @ 100-3500 Hz

